



Safety Data Sheet

Issue Date: 02-Jan-2013

Revision Date: 26-Mar-2020

Version 2

1. IDENTIFICATION

Product identifier

Product Name PC-11 Heavy Duty Epoxy Paste, Part A

Other means of identification

SDS # 130205-22C

UPC Code 054983 01011, 054983 02011, 054983 08011, 054983 16011, 054983 64011, 054983 12811

Recommended use of the chemical and restrictions on use

Recommended Use Multi-purpose epoxy paste.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency telephone number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance White paste

Physical state Paste

Odor None

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word

Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical name	CAS No	Weight-%
Bisphenol A - Epichlorohydrin polymer	25068-38-6	40-70
Kaolin	1332-58-7	10-30
Talc	14807-96-6	10-25
Titanium dioxide	13463-67-7	5-15
Soda lime borosilicate glass	65997-17-3	1-5
Ceramic Fiber	142844-00-6	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

* Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).
 (Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state.

4. FIRST AID MEASURES

Description of first aid measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye irritation. Direct contact may cause temporary redness and discomfort. Causes skin irritation. May cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Skin and eye conditions may be aggravated by long term exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Aldehydes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class III B.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/protective clothing and eye/face protection. Avoid breathing vapors, mist or gas. Remove any contaminated clothing and wash thoroughly before reuse.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using this product. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.
Incompatible Materials	None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Soda lime borosilicate glass 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable fraction	-	-
Ceramic Fiber 142844-00-6	TWA: 0.2 fiber/cm ³ respirable fibers: length >5 µm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination	-	-

Other Information	If product is sanded, appropriate respirator should be worn to avoid breathing dust. Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate silica / titanium dust. Inhaled silica / titanium has been classified by IARC as a human carcinogen (see section 11).
--------------------------	--

Appropriate engineering controls

Engineering Controls	Provide general or local exhaust ventilation if product is sanded or ground. Maintain eye wash fountain and quick-drench facilities in work area.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. If engineering controls do not keep airborne concentrations below acceptable levels, wear a NIOSH-approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste		
Appearance	White paste	Odor	None
Color	White	Odor Threshold	Not determined
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	> / = 2.0 - < / = 12.0		
Melting point / freezing point	Not available		
Boiling point / boiling range	Not available		
Flash point	248.88 °C / 480 °F		
Evaporation Rate	0		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Not available		
Lower flammability or explosive limits	Not available		
Vapor Pressure	0		
Vapor Density	Not available		
Relative Density	1.03	@ 60°F (ASTM D 1298)	
Water Solubility	Insoluble in water		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	Not determined		
Decomposition temperature	Not determined		
Kinematic viscosity	Not determined		
Dynamic Viscosity	5-10 million cps		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

Other information

Liquid Density 8.6 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation. May cause an allergic skin reaction.
Inhalation	May cause irritation of respiratory tract.
Ingestion	May cause discomfort if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A - Epichlorohydrin polymer 25068-38-6	= 11400 mg/kg (Rat)	20000 mg/kg (rabbit)	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Formaldehyde, polymer with 1,3,dimethylbenzene 26139-75-3	>2000 mg/kg (rat)	-	-
Polyethylene 9002-88-4	> 2000 mg/kg (Rat) = 8 g/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Ceramic Fiber is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		X
Titanium dioxide 13463-67-7		Group 2B		X
Soda lime borosilicate glass 65997-17-3		Group 3		
Ceramic Fiber 142844-00-6	A2	Group 2B	Reasonably Anticipated	X
Polyethylene 9002-88-4		Group 3		

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)
- A2 - Suspected Human Carcinogen
- IARC (International Agency for Research on Cancer)
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 IARC components are "not classifiable as human carcinogens"
- NTP (National Toxicology Program)
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)
- X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document Values exceed classification criteria.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

- Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
- DOT** Not regulated
- IATA** Not regulated
- IMDG** Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Bisphenol A - Epichlorohydrin polymer	X	ACTIVE	X	X	X	X	X	X	X
Kaolin	X	ACTIVE	X	X		X	X	X	X
Talc	X	ACTIVE	X	X	X	X	X	X	X
Titanium dioxide	X	ACTIVE	X	X	X	X	X	X	X
Formaldehyde, polymer with 1,3-dimethylbenzene	X	ACTIVE	X		X	X	X	X	X
Soda lime borosilicate glass	X	ACTIVE	X	X	X	X	X	X	X
Ceramic Fiber						X			
Polyethylene	X	ACTIVE	X		X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ceramic Fiber - 142844-00-6	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Kaolin 1332-58-7	X	X	X
Talc 14807-96-6	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Ceramic Fiber 142844-00-6	X		

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards 1	Flammability 1	Instability 0	Special Hazards Not determined
<u>HMIS</u>	Health Hazards 1	Flammability 1	Physical hazards 0	Personal Protection Not determined

Issue Date: 02-Jan-2013
 Revision Date: 26-Mar-2020
 Revision Note: Regulatory update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Issue Date: 02-Jan-2013

Revision Date: 30-Mar-2020

Version 2

1. IDENTIFICATION

Product identifier

Product Name PC-11 Heavy Duty Epoxy Paste, part B

Other means of identification

SDS # 130205-21C

UPC Code 054983 01011, 054983 02011, 054983 08011, 054983 16011, 054983 64011, 054983 12811

Recommended use of the chemical and restrictions on use

Recommended Use Multi-purpose epoxy paste.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency telephone number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Light blue paste **Physical state** Paste **Odor** Slight amine

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word

Warning

Hazard statements

Harmful if swallowed
Harmful in contact with skin
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 Call a poison center or doctor/physician if you feel unwell
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical name	CAS No	Weight-%
Styrenated phenol	61788-44-1	10-30
Talc	14807-96-6	25-35
Kaolin	1332-58-7	1-10
1-(2-Aminoethyl) piperazine	140-31-8	1-10
Soda lime borosilicate glass	65997-17-3	1-5
Ceramic Fiber	142844-00-6	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if necessary.

Ingestion Do NOT induce vomiting. Call a poison center or doctor/physician if you feel unwell. Rinse mouth. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms Harmful in contact with skin. Harmful if swallowed. Causes eye and skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Skin and eye conditions may be aggravated by long term exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Aldehydes. Nitrogen oxides (NOx).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/protective clothing and eye/face protection. Remove any contaminated clothing and wash thoroughly before reuse.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place.
Incompatible Materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Kaolin 1332-58-7	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Soda lime borosilicate glass 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable fraction	-	-
Ceramic Fiber 142844-00-6	TWA: 0.2 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination	-	-

Appropriate engineering controls

Engineering Controls	Provide general or local exhaust ventilation if product is sanded or ground. Maintain eye wash fountain and quick-drench facilities in work area.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. If engineering controls do not maintain airborne concentrations below recommended exposure limits, a NIOSH/MSHA approved respirator must be worn. Refer to 29 CFR 1910.134 for respiratory protection requirements.
General Hygiene Considerations	Avoid contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste	Odor	Slight amine
Appearance	Light blue paste	Odor Threshold	Not determined
Color	Light blue		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	> / = 2.0 - < / = 12.0		
Melting point / freezing point	Not determined		
Boiling point / boiling range	Not determined		
Flash point	> 110 °C / > 230 °F		
Evaporation Rate	0		
Flammability (Solid, Gas)	Not determined		
Flammability Limit in Air			
Upper flammability or explosive limits	Not determined		
Lower flammability or explosive limits	Not determined		
Vapor Pressure	0		
Vapor Density	Not determined		
Relative Density	1.01		
Water Solubility	Insoluble in water		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Autoignition temperature	Not determined		
Decomposition temperature	Not determined		
Kinematic viscosity	Not determined		
Dynamic Viscosity	5-10 million cps		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes eye irritation.
Skin Contact	Causes skin irritation. May cause an allergic skin reaction. Harmful in contact with skin.
Inhalation	May cause irritation to the mucous membranes and upper respiratory tract.
Ingestion	Harmful if swallowed. Ingestion may cause irritation to mucous membranes.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Styrenated phenol 61788-44-1	2100 - 6700 mg/kg (Rat)	> 7940 mg/kg (Rabbit)	> 2.5 mg/L (Rat) 6 h
Polyoxypropylenediamine 9046-10-0	= 1100 mg/kg (Rat)	= 1555 mg/kg (Rabbit)	-
Formaldehyde, polymer with 1,3,dimethylbenzene 26139-75-3	>2000 mg/kg (rat)	-	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
1-(2-Aminoethyl) piperazine 140-31-8	= 2140 µL/kg (Rat)	= 880 µL/kg (Rabbit)	-
Polyethylene 9002-88-4	> 2000 mg/kg (Rat) = 8 g/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Please see section 4 of this SDS for symptoms.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	May cause an allergic skin reaction.
Carcinogenicity	Ceramic Fiber is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		X
Soda lime borosilicate glass 65997-17-3		Group 3		
Polyethylene 9002-88-4		Group 3		
Ceramic Fiber 142844-00-6	A2	Group 2B	Reasonably Anticipated	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Oral LD50	1,639.34 mg/kg
Dermal LD50	1,404.49 mg/kg

12. ECOLOGICAL INFORMATION**Ecotoxicity**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	
1-(2-Aminoethyl) piperazine 140-31-8	495: 72 h Pseudokirchneriella subcapitata mg/L EC50	100: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 1950 - 2460: 96 h Pimephales promelas mg/L LC50 flow-through 1000: 96 h Poecilia reticulata mg/L LC50 semi-static	32: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Styrenated phenol 61788-44-1	4
1-(2-Aminoethyl) piperazine 140-31-8	-1.48

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Styrenated phenol	X	ACTIVE	X	X	X	X	X	X	X
Talc	X	ACTIVE	X	X	X	X	X	X	X
Polyoxypropylenediamine	X	ACTIVE	X		X	X	X	X	X
Formaldehyde, polymer with 1,3-dimethylbenzene	X	ACTIVE	X		X	X	X	X	X
Kaolin	X	ACTIVE	X	X		X	X	X	X
1-(2-Aminoethyl) piperazine	X	ACTIVE	X	X	X	X	X	X	X
Amine Terminated Liquid Copolymer	X	ACTIVE	X		X	X	X	X	X
Soda lime borosilicate glass	X	ACTIVE	X	X	X	X	X	X	X
Polyethylene	X	ACTIVE	X		X	X	X	X	X
Ceramic Fiber						X			

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Not determined

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ceramic Fiber - 142844-00-6	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	X	X	X
Kaolin 1332-58-7	X	X	X

1-(2-Aminoethyl) piperazine 140-31-8	X	X	X
Ceramic Fiber 142844-00-6	X		

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	2	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	1	0	Not determined

Issue Date: 02-Jan-2013
 Revision Date: 30-Mar-2020
 Revision Note: Regulatory update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet