4 / 4 11

For Non-Health Hazard Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

LEAD FREE*

Series LFN9

Dual Check Vacuum Breakers for In-Line Applications

Size 1/4", 3/8", 1/2"

Series LFN9 Dual Check Vacuum Breakers for In-Line Applications are used for continuous pressure, non-health hazard, applications. These valves have NPT female inlet and outlet connection and Lead Free* brass body construction. The LFN9 features Lead Free* construction to comply with Lead Free* installation requirements.

Options


LFN9C - Chrome body


Pressure - Temperature

Temperature Range: 33°F – 140°F (0.5°C – 60°C) Maximum Working Pressure: 125psi (8.6 bar)

Applications

Series LFN9 should be installed on each parlor sink where a hose is attached. This series is for use on continuous pressure applications.





Standards

CSA B64.8

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



LFN9

С	Capacity N9 Flow Chart						
	⁵⁰ T						
	45						
(psi)	40						
	35						
9	30						
Pressure Drop (psi)	25						
essi	20						
F	15						
	10						
	5 -						
	١٥						
	Č	1 2 3 4 5 6	7				
		Flow (gpm)					

Dimensions — Weights

MODEL	SIZE	DIMENSIONS					WEIGHT		
		Α		В		B1			
	in.	in.	mm	in.	mm	in.	mm	lbs.	kgs
LFN9	1/4	23/8	60	11/4	32	1	25	.38	.17
LFN9	3/8	23/8	60	11/4	32	1	25	.38	.17
LFN9	1/2	2%	60	11/4	32	1	25	.38	.17

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

NOTICE

Inquire with governing authorities for local installation requirements

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com **Canada:** T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca **Latin America:** T: (52) 81-1001-8600 • Watts.com

ES-LFN9 1804 © 2018 Watts