

### **CODE NUMBER**

3325500

### **DESCRIPTION**

Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Battery, Infrared, Exposed Sensor Urinal/Water Closet Retrofit Flushometer.

### **DETAILS**

• Finish: Polished Chrome (CP)

Power Type: BatteryBattery Life: 3 yearsValve: Diaphragm/Piston

Fixture Type: Urinal/Water ClosetFixture Connection: Top Spud

## **FEATURES**

- ADA Compliant Battery powered infrared side mount sensor for automatic "No Hands" operation
- Four (4) size C batteries included
- Non-Hold-Open True Mechanical Override Full Flush Button
- "Low Battery" Flashing LED
- "User in View" Flashing LED
- 72-Hour Sentinel Flush
- Estimated battery life 3 years at 4000 cycles per month
- Sensor with Automatic Range Adjustment



### **COMPLIANCES & CERTIFICATIONS**



BREEAM





(ADA Compliant, BREEAM Water Credit, cUPC Certified, Green Globes Water Credit)

### **ELECTRICAL SPECIFICATIONS**

• Arming Delay: 1-3 seconds

• Battery Life: 3 years

 Control Circuit: 6 VDC Input/72 Hour Sentinel Flush/Solid State

• Sensor Range: 22"-42" (559-1,067mm)

## **VALVE OPERATING PRESSURE (FLOWING)**

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

### **DOWNLOADS**

- EBV-500/550-A Installation Instructions
- EBV500/EBV550 Repair and Maintenance Guide
- Additional Downloads

### NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the EBV500A product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer. Find a compatible water closet for this flushometer.

Battery life varies according to actual usage and restroom conditions.

## WARRANTY

View Warranty Information



# **ROUGH-IN**

